





Please read instructions before commencing installation and retain for future reference.



4

Connecting the Terminal Block

Connect main supply (brown - live, blue - neutral) into terminal block making sure all connections are tight.



SPECIFICATIONS:

- **Fitting:** Aluminum.
- **Lamp type:** LED 3W 3000K 150LM.
Lamps and gears excluded unless otherwise specified.
- **Protection against electric shock:** CLASS II.
- **Ingress Protection:** IP20. Protection against entry of solid objects greater than 12mm in diameter.
- **Quality/Corrosive rating:** QC21: Burning period: 12hrs/24hr cycle. Commercial use, indoor mainly - painted or plated metals. Not for use in corrosive environments.
- **Driver:** Included.


INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, or damage to property. Installation of this product must be carried out by a qualified electrician.

- Ensure main supply is switched off.
- Insert masonry plugs (1) into mounting surface.
- Fit mounting bracket(2) onto mounting surface with self-tapping screws(3).
- Connect main supply wires to terminal block (4) making sure all connections are tight.
- Fit wall plate (6) onto mounting bracket with screws(5).
- Reconnect power.

WARNING:

- Not for outdoor use or in wet conditions.



IP20

0,5m

