




Please read instructions before commencing installation and retain for future reference.



### Connecting the Terminal Block

Connect main supply (brown - live, blue - neutral, green/yellow - earth) into terminal block making sure all connections are tight.

### SPECIFICATIONS:

- **Fitting:** ALUMINUM
- **Lamp type:** LED 12W 3000K
- **Protection against electric shock:** CLASS I,. Requires earth connection.
- **Ingress Protection:** IP20. Protection against entry of solid objects greater than 12mm in diameter.
- **Quality/Corrosive rating:** QC21: Burning period: 12hrs/24hr cycle. Commercial use, indoor mainly - painted or plated metals. Not for use in corrosive environments.
- **Driver:** Included.

### INSTALLATION INSTRUCTIONS:

**⚠** Electrical products can cause death, injury, or damage to property. Installation of this product must be carried out by a qualified electrician.

- Ensure mains supply is switched off.
- Insert masonry plugs(1) into mounting surface.
- Fit mounting bracket onto mounting surface with self-tapping screws (2).
- Connect wires according to color (White to White, Black to Black).  
Connect all earth lug together onto the crossbar with green screw to tight.
- Fit ceiling plate onto mounting bracket with nuts (4).
- Reconnect power.

### WARNING:

- Not for outdoor use or in wet conditions.

