


### Connecting the Terminal Block

Connect main supply (brown - Live, blue - Neutral) into terminal block making sure all connections are tight.



## PENDANT LIGHT

## 22150

Please read instructions before commencing installation and retain for future reference.

### SPECIFICATIONS

- **Material:** Metal + Opal Glass
- **Lamp type:** 3x E27 , MAX 40W / Bulb
- **Ingress Protection:** IP20. Protection against entry of solid objects greater than 12mm in diameter.

### INSTALLATION INSTRUCTIONS

**!** Electrical products can cause death, injury, or damage to property. Maintenance and installation should only be carried out by a professional electrician.

- Ensure main supply is switched off.
- Insert masonry plugs (1) into mounting surface.
- Fit mounting bracket onto mounting surface with self-tapping screws (2).
- Connect main supply wires to terminal block (3) making sure all connections are tight.
- Insert masonry plugs (4) into mounting surface.
- Fit the bezel (5) and secure by screwing the safety caps (6).
- Steps 4, 5 and 6, repeat three times from left to right.
- Then secure the cables over the bezel and into the recesses of the base (7).
- The light is adjustable, place the cables in the position that works for you.
- Fit ceiling plate onto mounting bracket with screws (8).
- Use the rings to secure all glass shades on the lamp-holders (9).
- Install all E27 lamps into the lamp-holders (10).
- Reconnect power.

### WARNING

- Make sure that the products is installed properly before connecting to electricity.
- Do not cover the fitting.
- Not for outdoor use or in wet conditions.
- Do not exceed the maximum wattage rating of the lamp.